

31. The improved fish hook of Claim 29 wherein the second shank comprises a second hook.
32. The improved fish hook of Claim 30 wherein the first hook further comprises a barb disposed about the second end of the first hook.
33. The improved fish hook of Claim 31 wherein the second hook further comprises a barb disposed about the second end of the second hook.
34. The improved fish hook of Claim 29 wherein the tensioner comprises a spring.
35. The improved fish hook of Claim 29 wherein the tensioner comprises a coil.
36. The apparatus of claim 29 wherein the tensioner comprises one or more coils of said single wire.
37. The improved fish hook of Claim 29 further comprising a prong along the first shank.
38. The improved fish hook of Claim 29 wherein the second position disposes the first shank and the second shank substantially parallel and the second position disposes the first shank and the second shank crossed.
39. The improved fish hook of Claim 37 wherein the prong comprises a body.
40. The improved fish hook of Claim 29 further comprising an eyelet disposed about and intermediate the first shank and the second shank.

41. The improved fish hook of Claim 29 wherein the latch may be released upon the application of two generally opposing forces applied along the first shank and the second shank.

42. The improved fish hook of Claim 41 wherein the two generally opposing forces are generally in a direction of one another.

43. The improved fish hook of Claim 29 wherein the latch is disposed about the tensioner.

44. The improved fish hook of Claim 29 wherein the latch is disposed proximate the first end of the first shank and the first end of the second shank and releasably in communication with the tensioner.

45. The improved fish hook of Claim 29 wherein the tensioner further comprises a brad.

46. The improved fish hook of Claim 45 wherein the brad comprises a hollow bore brad.

47. The improved fish hook of Claim 29 wherein the wire comprises a metal.

48. The improved fish hook of Claim 47 wherein the metal is selected from the group consisting of steel, iron, aluminum, copper, an alloy of steel, an alloy of iron, an alloy of aluminum, an alloy of copper and combinations thereof.

49. The improved fish hook of Claim 29 wherein the wire comprises a composite material.

50. An improved releasably biasable apparatus formed from a single piece of wire comprising:

a first shank having a first end and a second end;

a second shank having a first end and a second end;